




ADSL Transformers for Conexant Chipsets



Features

- complies with ANSI and ETSI requirements
- matched to Conexant's 328R58-001 & 328R57-001 chipsets
- very low THD
- 1500V minimum isolation
- all materials approved to UL94V-0
- excellent quality at competitive price due to high volume production
- manufactured in ISO-9001:2000, TS-16949:2002 and ISO-14001:2004 certified Talema facility
- fully RoHS compliant and meets lead free reflow level J-STD-020C




Electrical Specifications @ 25°C • Operating Temperature -40° to +85°C

Part Number	Package	IC Driver	Turns Ratio ±2% Line : IC	L _p (μH) ±10%	L _L (μH) Max	C _{wv} (pF) Max	DCR (Ohms) Max Line / IC	THD (Linearity) Typical 100kHz	Longitudinal Balance Min 25kHz-1MHz	Insertion Loss Max 100kHz	Frequency Response Max 30kHz- 1.1MHz	Isolation Voltage (Vrms) 1500
AEP1100-T	TH	328R58-001 CO/CPE	2 : 1	800	10	50	1.48 / 0.77	-80dB	-40dB	0.5dB	1.0dB	1500
AEP1100-S	SMD	328R57-001 CO/CPE										



Schematic



Dimensions: Inches(Millimeters)
Tolerance: ±0.010 (0.25)

Weight: 6.8 grams

Sales & Marketing, Design and Manufacturing Facilities

<http://www.talema-nuvotem.com>

Eastern Europe & Czech Republic

NT MAGNETICS s.r.o.
Chebská 27
322 00 Plzeň
Tel: Int. + 420 37 - 744 9303
Fax: Int. + 420 37 - 744 3697
Email: talema@talema.cz

Germany

TALEMA ELEKTRONIK GMBH
Sembdnerstr. 5, Postfach 2523
82110 Germering
Tel: Int. + 49 89 - 841 00 - 0
Fax: Int. + 49 89 - 841 00 25
Email: info@talema.de

Ireland

NUVOTEM TEO.
Crolly
Co. Donegal
Tel: Int. + 353 74 - 954 8666
Fax: Int. + 353 74 - 954 8139
Email: info@nuvotem.com

India

TALEMA ELECTRONIC PVT. LTD.
Opposite the SIDCO Industrial Estate
Gins Towers
4/5S.H/1, Omalur Main Road
Salem - 636 004, Tamil Nadu
Tel: Int. + 91 427 - 244 1325
Fax: Int. + 91 427 - 243 0034
E-mail: talema@talemaindia.com