



## ATM 25MBPS Pulse Transformer for Novacom & SEEQ PHY Interface

### Features

- Meets ATM 25.6 PHY specifications providing compatibility with Novacom NOV25PMD6 and SEEQ 93C95 PHY interface
- Impedance matching for 100 ohm UTP applications
- Low profile, light weight SMD packages for high density board placement
- Designed for pick and place compatability while providing consistant and reliable coplanarity
- Excellent quality at extremely competitive price due to high volume production
- Manufactured in an ISO-9001:2000, TS-16949:2002 and ISO-14001:2004 certified Talema facility
- Fully RoHS compliant and meets lead free reflow level J-STD-020C



### Electrical Specifications @ 25°C

Operating Temperature Range: -40°C to +85°C

Storage Temperature: -40°C to +125°C

Minimum isolation voltage: 1500 Vrms


Standard Packaging: Tape & Reel

Quality and consistency is guaranteed through 100% testing of the specified parameters for primary inductance, leakage inductance, turns ratio, DC resistance and interwinding capacitance. This ensures that the return loss and pulse wave shape requirements can be fully maintained. Additionally, all parts are tested for 1500V minimum isolation.

### Pulse Transformer for Impedance matching for 100 ohm UTP Applications


Part Number	Turns Ratio ±2%		OCL (µHMin.)	L <sub>L</sub> (µH max)	C <sub>WW</sub> (pF max)	DCR (Ohms max)
UTM-3000-J	1:1	1ct:1	3000	1.6	55	1.3

### UTM Miniature Module




Surface coplanarity 0.004 (0.10) maximum

### Suggested Pad Layout



### Schematic



Dimensions: Inches (Millimeters)

Tolerance: ±0.010 (0.25) unless specified otherwise

## Sales & Marketing, Design and Manufacturing Facilities

<http://www.talema-nuvotem.com>

### Eastern Europe & Czech Republic

NT MAGNETICS s.r.o.  
Chebská 27  
322 00 Plzeň  
Tel: Int. + 420 37 - 744 9303  
Fax: Int. + 420 37 - 744 3697  
Email: talema@talema.cz

### Germany

TALEMAELEKTRONIK GMBH  
Sembdnerstr. 5, Postfach 2523  
82110 Germering  
Tel: Int. + 49 89 - 841 00 - 0  
Fax: Int. + 49 89 - 841 00 25  
Email: info@talema.de

### Ireland

NUVOTEMTEO.  
Crollly  
Co. Donegal  
Tel: Int. + 353 74 - 954 8666  
Fax: Int. + 353 74 - 954 8139  
Email: info@nuvotem.com

### India

TALEMAELECTRONIC PVT. LTD.  
Opposite the SIDCO Industrial Estate  
Gins Towers  
4/5S.H/1, Omalur Main Road  
Salem - 636 004, Tamil Nadu  
Tel: Int. + 91 427 - 244 1325  
Fax: Int. + 91 427 - 243 0034  
E-mail: talema@talemaindia.com

THE TALEMA GROUP • Magnetic Components for ISDN / xDSL / LAN Data Communications